

Uniclass L331	EPIC C311	Feb 06
CI/SfB	Eq4	

Castle Readybag Post Mate technical specification

Castle Readybag Post Mate is formulated to produce good quality post hole concrete for setting all types of posts.

Applications

Castle Readybag Post Mate is a good quality post hole concrete for setting all types of posts including treated wood/metal posts or supports, concrete and plastic posts.

- Easy to use – just add water
- Saves time – quick and convenient
- Economic – less waste than some other methods

Quality



Castle Readybag Post Mate is factory produced to ensure the highest quality post hole concrete.

One bag is sufficient to support a post in a hole measuring 250mm x 250mm x 350mm.

Instructions for use

Single posts

1. Dig a hole approximately one spade square, one and a half spades deep (10ins x 10ins x 14ins or 250mm x 250mm x 350mm).
2. Position post vertically in hole, pour half the contents of the bag into the hole around the post. **DO NOT MIX.**
3. Use a watering can to pour approximately 2 litres of water onto the base of the post, at the level of the Post Mate.
4. After 2 minutes, check the vertical position of the post by using a spirit level on the front and side faces. Adjust position of post.
5. Pour the rest of the Post Mate into the hole, followed by a further 2 litres of water which should be directed onto the post at ground level.
6. Allow the Post Mate to harden prior to carrying out further work.



Multi fence post panels

- a. Dig a hole for post and follow stages 1-4 above.
- b. Measure position of subsequent holes and dig out.
- c. Fix panels and posts adjusting verticals as necessary.
- d. Apply stages 1-4 above as you go along.
- e. Apply stage 5 to all posts.

Large fence posts

For posts over 7 foot (2100mm) simply increase the hole depth and add rubble/ broken bricks around the base of the post. Follow steps d-e above, as one bag can be used for any size post.

Addition of other materials

Castle Readybag Post Mate is a pre-packed post hole concrete. The addition of admixtures is not recommended and could adversely affect the performance of the finished product.

For further information please contact:

Castle Cement Limited
Park Square 3160 Solihull Parkway
Birmingham Business Park
Birmingham B37 7YN

Technical Helpline:

tel: 0845 722 7853
(calls charged at local rate)

fax: 01780 727154

technical.help@castlecement.co.uk

Customer Services:

tel: 0845 600 1616
(calls charged at local rate)

fax: 0121 606 1436

customer.services@castlecement.co.uk

Please note: Reference to a Technical Standard number in this leaflet is deemed to include the latest published edition and/or any published amendments issued after the standard's publication, unless a date of issue is quoted in which case reference is to the provisions stated in that edition.

L006(D)/02/06/pdf