

A close-up photograph of a brick wall. The bricks are a light tan or yellowish-brown color with a rough, textured surface. They are laid in a standard running bond pattern. The mortar joints are a light grey color. In the bottom left corner, there is a white rectangular overlay containing text.

— THE ORIGINAL —
London

Nene Valley Stone

Nene Valley Stone

Manufactured to BS EN 771-1

Brick type

Category II, HD, Clay Masonry Unit

Standard work size

215 x 102.5 x 65mm

Dimensional tolerances

Tolerance category: T2

Range category: R1

Compressive strength

$\geq 25\text{N/mm}^2$

Water absorption

$\leq 23\%$

Durability

F1

Active soluble salts content

S2

Configuration

Frogged 15-20% voids

Dry weight per brick

1.95kg

Pack size

390

This panel is printed on paper made using ecf from fibres obtained from a sustainable timber source.

DISCLAIMER:

The reproduction of colours and textures is only as accurate as the printing process will allow. Photographic samples should be used when shortlisting products but we advise that an actual sample should be seen before ordering.



— THE ORIGINAL —
London



Hanson Building Products
222 Peterborough Road
Whittlesey
Cambridgeshire
PE7 1PD

Tel: 08705 258258
Fax: 01234 762040

www.hanson.com/uk